



Web Argentina





Web Uruguay



Web Paraguay

SPECIFICATION

| S.N. | ITEMS & DESCRIPTION | IMAGE |
|------|---|-------|
| | Mass Flow Meter CG-15 | |
| | Specifications of sensor | |
| | Fluid temperature -200~+200°C | |
| | End connection Nut, M32x1.5 | |
| | Vibrating tube Stainless steel 316L | |
| | Sensor housing Stainless steel 304 | |
| | Splitter & flange Stainless steel 304 | |
| | Ex-mark  II 2G Ex ib IIC T6...T1 Gb | |
| | Specifications of transmitter | |
| | Operating temp. -30°C~+60°C | |
| | RH ≤95%, non condensing | |
| | Atmospheric Pressure 86~106 kPa | |
| | Operating voltage AC85~265V or DC12~24V | |
| | Output RS485 Modbus RTU, Pulse | |
| | Ex-mark  II 2G Ex db [ib] IIC T6...T1 Gb | |
| 1 | Specifications of mass flow meter | |
| | Model No. CG-15 | |
| | Max. flow rate 50kg/min | |
| | Nominal diameter 15mm | |
| | MWP. 25MPa | |
| | Zero stability 0.12kg/h | |
| | Repeatability 0,05 % | |
| | Liquid accuracy ±0.2% | |
| | Gas accuracy ±0.5% | |
| | Temp. accuracy ±1°C ±0.5% of reading | |
| | Density accuracy ±0.002g/cm ³ | |
| | Rangeability 1:20 | |
| | Ingress protection IP67 | |
| | Warranty 2-year | |
| | Certificate CE, ATEX | |
| | Package size 445*370*405mm | |
| | G.W. 12kgs | |

