



SS2100 TDL GAS ANALYZER

KEY FEATURES

- Laser based – rapid response
- Negligible interference from contaminants
- Non-contact sensing
- Reliable in harsh environments
- Low maintenance
- Intrinsically stable; Field calibration not needed
- Remote diagnostics
- Available for H₂O, CO₂, H₂S, NH₃ & C₂H₂ measurements
- CSA Class I, Div 2 certified



SpectraSensors SS2100 Process Gas Analyzers are exceptionally reliable for measuring trace gas components using Tunable Laser Diode (TDL) technology. TDL absorption spectroscopy is a high-resolution infrared technique that enables the measurement of specific gases with precision while avoiding interferences that are common with traditional infrared analyzers. The SS2100 is certified for CSA Class I, Div 2.

SIMPLE OPERATION

The operation of the analyzer is very straightforward. Most technical personnel can learn to operate the system in a very brief time. Coupled with the fact the analyzer has very little maintenance requirements, the end result is an extremely low cost of ownership. At the same time, technical support capability is a crucial element of the product design. There are several health monitoring parameters and remote access is available using AMS100™ software or directly through the touch sensitive keypad.

RELIABLE

Trustworthy measurements are vital in process analytical applications. The TDL sensor is unaffected by contaminants and corrosives since the gas stream never touches the laser or detector. The SS2100 requires little maintenance and does not need recalibration or periodic replacement parts due to the inherent stability of TDL technology.

SIMPLE INSTALLATION

The SS2100 is easy to install; connect the power, data link and measured gas line and the analyzer begins working without the need for extensive calibrations or setup.



**SS2100 Examples
Trace H₂S (left) Trace H₂O (right)**

SS2100 TDL Gas Analyzer

SPECIFICATIONS

Application Data

Target Components	H ₂ O, H ₂ S, CO ₂ , NH ₃ , C ₂ H ₂ (Ranges from low ppmv to %)*
Principle of Measurement	Tunable Diode Laser Absorption Spectroscopy
Measurement Time	Typically less than 20 seconds*
Environmental Temperature Range	-20°C to +50°C , -10°C to +60°C - <i>optional</i>
Sample Cell Pressure Range	Typically 800-1200 mbar or 950-1700 mbar* - <i>optional</i>
Pressure to Sample Cabinet	Typically between 140-350 kPaG (20-50 PSIG)*
Sample Flow Rate	0.5-4 SLPM (0.02-0.1 SCFM)*
Relative Humidity	5% to 95%, Non-Condensing



Electrical & Communications

Input Power, Maximum	120 or 240 VAC +/-10%, 50-60 Hz, 300W - <i>standard</i> 18 - 24VDC, 1.6A max - <i>optional</i>
Analog Communication	Isolated 4-20mA Analog Output, 1200 ohms @ 24 VDC max
Serial Communications	RS232C and Ethernet
Digital Outputs	Qty 5: Concentration Alarm, General Fault, Validation Fail*, Validation 1 Active*, Validation 2 Active*
DO Contact Rating (inductive)	250VAC, 3A NO Contact, 1.5A NC Contact 24VDC, 1A NO and NC Contact
Digital Inputs	Qty 2: Flow Alarm*, Validation Request*
Protocol	Modbus Gould RTU or Daniel RTU or ASCII
Diagnostic Value Examples	Detector Power (Optics Health), Spectrum Reference Comparison and Peak Tracking (Spectrum Quality), Cell Pressure and Temperature (Overall System Health)
LCD Display	Concentration, Cell Pressure and Temperature & Diagnostics

Physical

Electronics Enclosure	NEMA4X 304 or 316L Stainless Steel
Sample System Enclosure(s)	NEMA4X 304 or 316L Stainless Steel
Analyzer Dimensions	1300-1500mm H x 600-920mm W x 300-450mm D (50-60 H x 24-36 W x 12-17 D inches) with Sample System*
Analyzer Weight	90-130 kg (200-300 lbs) with Sample System*
Sample Cell Construction	316L Series Polished Stainless Steel
Number of Sample Cells	1 per Analyzer

Certifications

Analyzer (Electronics & Laser)	CSA Class I, Div 2, Groups A, B, C & D, T3C, Type 4X and IP65
Analyzer with Sample Conditioning System	Assembled using electrical components which are certified for Class I, Div. 2, Groups B, C & D, T3 or better.

*Application dependent.

SpectraSensors

4333 W Sam Houston Pkwy N, Ste 100
Houston, TX 77043
Tel: +1 800 619-2861
Direct: +1 713 300-2700 Fax: +1 713 856-6623



www.spectrasensors.com

DS SS2100 TDL EN (9/14)