

# airmoVOC C<sub>2</sub>C<sub>6</sub>

Designed for analysis + monitoring of "light" hydrocarbons. It is used for the measurement of volatile hydrocarbon in the range of C<sub>2</sub> to C<sub>6</sub> i.e. from Ethane through 1,3-Butadiene up to Benzene (and other C<sub>6</sub> compounds).



**Model: A11000**

### Environment:

Urban / Non urban area pollution control  
Indoor measurements  
BTEX / PAMS / CE analysis  
Plant / process emissions

### Toxicity:

Benzene, 1,3-butadiene  
VOC screening of CO<sub>2</sub> quality for the food and beverage industry

### Process:

Industrial Hygiene  
Fence line monitoring  
Acetaldehyde/benzene

Butenes

Acetylene

Ethane

1,3-butadiene

Pentenes

**DASTECS** S.R.L.

Representantes / Distribuidores Exclusivos  
Buenos Aires, Argentina  
Tel.: (54 - 11) 5352-2500  
Email: info@dastecsrl.com.ar  
Web: www.dastecsrl.com.ar



Chromatotec® is specialised in VOC, Sulfur and permanent gases analysis at trace and ultra trace levels (ppm, ppb, ppt).  
Please visit our website for more details.

Updated: July 2013

# airmoVOC C<sub>2</sub>C<sub>6</sub>



Designed for analysis + monitoring of "light" hydrocarbons. It is used for the measurement of volatile hydrocarbon in the range of C<sub>2</sub> to C<sub>6</sub> i.e. from Ethane through 1,3-Butadiene up to Benzene (and other C<sub>6</sub> compounds).

## Principle:

The instrument uses a 6-port valve with a single sorbent trap, and a metallic capillary column. It has a minimum detection level as low as 15 ppt (for 1,3-Butadiene for e.g.) in ambient air, and analyses up to 32 compounds during a single analysis.

The airmoVOC C<sub>2</sub>-C<sub>6</sub> uses a thermoelectric cooling system to control the temperature of the sample trap when required, for example for the analysis of Ethyne.

Miniaturization, sensitivity, mobility and flexibility are its main features. Everything from the sample port up to the data storage is integrated in a 19"- rack 4U.

Programmed gradient temperature of the oven and pressure/flow control of the carrier gas by the piezo-valve.

Before delivery the analyser is tested for one week by our quality control department.

The Vistachrom software enables the user to view and store data on a PC. It provides comfortable user friendly utilities to recalculate, calibrate and export data and to configure the measurement.

The software allows the calculation of retention time, area, mass or concentration profiles.

### Example of analysed VOC's

PAMS Photochemical Assessment Monitoring Stations	USA	EUR
All VOC below can be analysed	20/55 AIRS FORMAT*	17/30
<b>Ethane C2</b>	43202	X
Ethylène/Ethene	43203	X
Acétylène/Ethyne	43206	X
<b>Propane C3</b>	43204	X
Propylène/Propène	43205	X
iso-butane (2-methyl propane)	43214	X
<b>N-butane C4</b>	43212	X
1-butène	43280	X
Iso-butene (2-methyl propene)	43215	
Trans-2-butène	43216	X
Propyne		
Cis-2-butène	43217	X
1,3 butadiène		X
Cyclopentane	43242	
iso-pentane (2-méthyl butane)	43221	X
<b>N-pentane C5</b>	43220	X
1-pentène	43224	X
Trans-2-pentène	43226	X
Cis-2-pentène	43227	X

## Product technical specifications:

### Light COV analysis:

- C<sub>2</sub> to C<sub>6</sub>

### Detection limit:

- 15 ppt for 1,3-Butadiene or 33 ng/m<sup>3</sup>

### Detection range:

- 0.033 to 500 µg/m<sup>3</sup> of 1,3-Butadiene

### Relative Standard Deviation:

- < 0.3 % over 48h (RT)
- < 3 % over 48 h (Conc.)

### Results:

- Data storage
- 4-20mA current output (option)
- MODBUS / JBUS or MGS1 communication protocol (option)

### Cycle time:

- 30 min as standard (20 min. optional)

### Gas supply:

- H<sub>2</sub> (FID and carrier gas): 30 ml/min (inlet 2 bars; 1/16" swagelock)
- Air (FID): 180 ml/min (inlet 3 bars; 1/8" swagelock)
- Sample inlet (vacuum pump) 1/4" swagelock

### Sample volume:

- 20 to 240 ml (programmable)

### Power supply:

- Main: 230V / 115V or 50 Hz / 60Hz
- Battery: 24V (option)

### Electrical consumption:

- Mean: 150 VA, peak 360 VA

### Dimensions and weight:

- Rack: 19" - (4U)
- Height: 180mm
- Width: 482mm
- Depth: 600mm
- Net weight : 17 Kg

**DASTEC** S.R.L.

Representantes / Distribuidores Exclusivos

Buenos Aires, Argentina

Tel.: (54 - 11) 5352-2500

Email: info@dastecsr.com.ar

Web: www.dastecsr.com.ar



## Options:

- On-line results are transmitted via a MODBUS / JBUS or MGS1 communication protocol
- Analog output 4-20 mA or 0-10 V
- **Automatic** validation / calibration
- 24 V power supply
- Hydrogen and zero air generator for transportable analysers.
- Multiple Stream selector (2 to 6)

## For ordering:

- airmoVOC C<sub>2</sub>C<sub>6</sub> (4U) (with internal cooling)  
Needs a 5U supervisor
- Supervisor (5U)  
Chromatotec® computer 5U, LCD display,  
Vistachrom software, 2 x RS232

## Model:

A11000  
XXX015

Chromatotec® is specialised in VOC, Sulfur and permanent gases analysis at trace and ultra trace levels (ppm, ppb, ppt). Please visit our website for more details.



To contact us: [info@chromatotec.com](mailto:info@chromatotec.com)

### NORTH AMERICA

CHROMATOTEC Inc.  
18333 Egret Bay Blvd, Suite 270,  
Houston TX 77058 - USA  
Phone: +1 (281) 335 4944  
Fax: +1 (281) 335 4943

### EUROPE

AIRMOTEC AG SAS  
15 rue d'Artiguelongue  
33240 Saint-Antoine - FRANCE  
Phone: +33 (0) 557 940 626  
Fax: +33 (0) 557 940 620

### ASIA

Chromatotec Trading (Beijing) Co., Ltd.  
Room 1806, Building 1,  
Wanda Plaza, No.93, Jianguo Avenue,  
Chaoyang District,  
Beijing 100022 - CHINA  
Phone: +86 (0) 105 960 3283